

IN THE CLAIMS:

- Sub 1
B1
1. (Original) A data storage library, comprising:
first and second arrays of storage cells, the storage cells in the first and second arrays being operable to receive data storage elements, the first and second arrays describing an interior space between at the first and second arrays; and
a third array of storage cells, the storage cells in the third array being operable to receive data storage elements, the third array being substantially located within the interior space;
wherein a robotic picker is translatable along a path, the path located within the interior space and comprising sections that pass adjacent to at least some of the arrays.
 2. (Withdrawn)
 3. (Original) The library of Claim 1, wherein the third array comprises two storage arrays arranged substantially back-to-back.
 4. (Original) The library of Claim 1, wherein when the robotic picker is positioned to access a storage element of the first array, it can rotate so as to access a storage element of the third array.
 5. (Original) The library of Claim 1, wherein the path has sections adjacent to each storage array of the library such that the robotic picker can access any storage array by translating to it along the path.
 6. (Original) The library of Claim 1 wherein the robotic picker has a bi-directional pass-through gripper that can access storage elements on two sides of the access device without rotating the access device.
 7. (Original) The Library of Claim 1, wherein the data storage elements are selected from the group consisting of magnetic tape cartridges, floppy disks, hard disks, and compact disks.

Subcl Cmt
B1
Cmt

8. (Original) A data storage library, comprising:
a storage area having a plurality of storage arrays, the arrays capable of storing individual data storage elements;
an access device capable of accessing data storage elements from the plurality of storage arrays, the access device being translatable along a path;
first and second storage arrays within the plurality of storage arrays positioned on opposite sides of the storage area facing each other; and
a third storage array within the plurality of storage arrays positioned substantially parallel to the first and second storage arrays and positioned between first and second storage arrays.

9. (Original) The library of Claim 8, wherein by translation along the path the access device can access data storage elements in the first and second storage arrays; and
wherein when the access device is positioned to access a storage element in the first storage array, the access device can perform a rotation to be positioned to access storage elements in the third storage array.

10. (Original) The library of Claim 8, further comprising a fourth storage array of the plurality positioned substantially parallel to the second storage array and positioned between the second and the third storage arrays, such that when the access device is positioned to access a storage element in the second storage array, the access device can perform a rotation to be positioned to access storage elements in the fourth storage array.

11. (Original) The library of Claim 8, wherein the path passes continuously past each of the storage arrays of the plurality such that the access device can access any storage array of the plurality by translating along the path.

12. (Withdrawn)

Sub C1 Cont
B1
Cont

13. (Original) The library of Claim 8, wherein the path is a track upon which the access device moves.

14. (Original) The library of Claim 8, wherein the access device has a bi-directional pass-through gripper that can access storage elements on two sides of the access device without rotating the access device.

15. (Original) The library of Claim 8, wherein the data storage elements are selected from the group consisting of magnetic tape cartridges, floppy disks, hard disks, and compact disks.

16. (Original) A data storage library, comprising:
first, second, third, and fourth storage arrays for holding data storage elements, all four storage arrays being substantially parallel to one another;
an access device capable of accessing data storage elements from the four storage arrays;
wherein when the access device is positioned to access storage elements from the first storage array, the access device can be rotated substantially 180 degrees to access storage elements from the second storage array; and
wherein when the access device is positioned to access storage elements from the third storage array, the access device can be rotated substantially 180 degrees to access storage elements from the fourth storage array.

17. (Original) The library of Claim 16, wherein the first and fourth storage arrays each face inward forming a space between them, and the second and third storage arrays are positioned substantially back-to-back within the space facing outward.

18. (Withdrawn)

- Subcl Cont*
B1
Cont
19. (Withdrawn)
20. (Original) The library of Claim 16, wherein the access device translates along a single path which passes adjacent to all storage arrays in the library.
21. (Original) The Library of Claim 16, wherein the data storage elements are selected from the group consisting of magnetic tape cartridges, floppy disks, hard disks, and compact disks.
22. (Original) A method of data storage, comprising:
positioning first, second, third and fourth storage arrays such that the four arrays are substantially parallel to one another, the second and third arrays being positioned substantially back-to-back and between the first and fourth arrays;
when a robotic picker is in a first orientation, translating the robotic picker along a path to access an individual data storage element from the first or fourth array; and
when the robotic picker is in the first orientation, translating the robotic picker along the path and rotating the robotic picker 180 degrees to access an individual storage element from the second or third storage array.
23. (Original) The method of Claim 22, wherein when the robotic picker is in a second orientation, translating the robotic picker along a path to access an individual data storage element from the second or third array; and
when the robotic picker is in the second orientation, translating the robotic picker along the path and rotating the robotic picker 180 degrees to access an individual storage element from the first or fourth storage array.
24. (Withdrawn)
25. (Original) The method of Claim 22, wherein the robotic picker is capable of translating and rotating simultaneously.

Sub C/ Concl.
B1
Concl.

26. (Original) The Library of Claim 22, wherein the data storage elements are selected from the group consisting of magnetic tape cartridges, floppy disks, hard disks, and compact disks.
